

### INSULATION NOTES:

PROVIDE AND INSTALL WHITE F-2 CAP SHEET UNDER BOTTOM OF ROOF DECK INSULATION. SEE SHEET A-103 FOR TOTAL ROOF INSULATION CALCULATION TO MEET I.E.C.C. REQUIREMENTS.



AT 6" OR LARGER METAL STUD FRAME WALLS, PROVIDE AND INSTALL R-19 BATT INSULATION FROM FLOOR TO BOTTOM OF ROOF DECK.

AT 3-5/8" METAL STUD FRAMED WALL (INTERIOR PARTITIONS), PROVIDE AND INSTALL R-13 ACOUSTIC INSULATION FLOOR TO TOP OF WALL.

AT EXTERIOR WALL FURRING WITHIN THE OFFICE SPACES, PROVIDE AND INSTALL R-13 BATT INSULATION FROM FLOOR TO TOP OF WALL FURRING (6" MINIMUM ABOVE HIGHEST ADJACENT CEILING), AND STICK-PIN R-13 BATT INSULATION TO THE EXTERIOR CONCRETE WALL FROM THE TOP OF WALL FURRING TO THE BOTTOM OF ROOF DECK WITH WHITE SCRIM SHEET COVER.

### FLOOR PLAN

SCALE: 1/16" = 1'-0"



### DOOR SCHEDULE:


(100 X TS)

SEE SHEET A-202 FOR DOOR SCHEDULE AND DOOR HARDWARE NOTES

### FIRE EXTINGUISHER NOTE:

THE CONTRACTOR SHALL PROVIDE TEMPORARY FIRE EXTINGUISHERS, 2A 10:BC, 5LBS. MINIMUM DURING THE COURSE OF CONSTRUCTION. PERMANENT EXTINGUISHERS AND THEIR LOCATIONS TO MEET THE MAXIMUM 75' TRAVEL DISTANCE IN THE WAREHOUSE WILL BE LOCATED AND SPECIFIED AS PART OF THE TENANT'S STORAGE SYSTEM IMPROVEMENTS. SEE OFFICE PLANS SHEET A-1-04 FOR OFFICE EXTINGUISHER LOCATIONS.

THIS DRAWING IS AN INSTRUMENT OF SERVICE AND IS THE PROPERTY OF BALMER ARCHITECTURAL GROUP INC. THIS DRAWING MAY NOT BE REPRODUCED NOR REPRODUCTION HEREOF USED, WITHOUT THEIR WRITTEN PERMISSION. © 2021 BALMER ARCHITECTURAL GROUP, INC. 2425 E. CAMELBACK RD., SUITE 775 PHOENIX, ARIZONA 85016 PH: 602-954-6718 FAX: 602-468-9860 E-MAIL: ADMIN@BAG-INC.COM



VIP PRODUCTS  
GOODYEAR, AZ.  
FLOOR PLAN

A-102  
40012.010  
25MAR21  
14MAY21  
CITY CORRECTIONS/  
COORDINATION

